

Number	Quantity	Description
31	3	Phoenix M1 Manual Gummed Tape Dispensers
32	3	Intermac Technologies PD42 Easy Coder/Printers
33	3	Intermac Technologies PD42 Easy Coder/Printers
34	4	Intermac Technologies PD42 Easy Coder/Printers
35	3	DataMax DMX-I-4212 Easy Coder/Printers
37	1	Cincinnati Milacron E-90-D-5 Blow Mold Injection Machine 15-25" Minimum Day Light, 35-45" Maximum Day Light, 20" Maximum Stroke, 50 Ton Clamp Force, Clear Platen Area: 40" Horizontal x 37" Vertical, 3.50 Extruder Size, 24:1 L/D Ratio, 6-125 RPM Screw Speed, 3 Heat Zones, Extruder Output: 550 lb./hr. (Based on HDPE with 0.96 Density and 0.3 Melt Index and 390 Degrees Fahrenheit Melt Temperature). 5.0 lb. Maximum Shot/Head, 8.0" Maximum Die Diameter S/N B72A0198003
38	1	Cincinnati Milacron E90-D5-01.5 Blow Mold Injection Machine 15-25" Minimum Day Light, 35-45" Maximum Day Light, 20" Maximum Stroke, 50 Ton Clamp Force, Clear Platen Area: 40" Horizontal x 37" Vertical, 3.50 Extruder Size, 24:1 L/D Ratio, 6-125 RPM Screw Speed, 3 Heat Zones, Extruder Output: 550 lb./hr. (Based on HDPE with 0.96 Density and 0.3 Melt Index and 390 Degrees Fahrenheit Melt Temperature). 5.0 lb. Maximum Shot/Head, 8.0" Maximum Die Diameter S/N B72A0100010
39	1	Cincinnati Milacron E90-S-D-8 Blow Mold Injection Machine 15-25" Minimum Day Light, 35-45" Maximum Day Light, 20" Maximum Stroke, 50 Ton Clamp Force, Clear Platen Area: 40" Horizontal x 37" Vertical, 3.50 Extruder Size, 24:1 L/D Ratio, 6-125 RPM Screw Speed, 3 Heat Zones, Extruder Output: 550 lb./hr. (Based on HDPE with 0.96 Density and 0.3 Melt Index and 390 Degrees Fahrenheit Melt Temperature). 8.5 lb. Maximum Shot/Head, 10.0" Maximum Die Diameter S/N B72A0194008
40	1	Cincinnati Milacron T2000V-150G-S75 Blow Mold Injection Machine Extruder Size: 150mm, L/D Ratio: 28:1, Screw Speed: 60 RPM, 74.8" Maximum Day Light, 15.7" Minimum Day Light, 59" Maximum Stroke, 60.2" x 82.6" Clear Platen Area, 220 Ton Clamp Force S/N B80A0100007
41	1	Hartig Blow Mold Injection Machine Single head, Shot size: 70lb Inverted, Platen size 48" x 72", Max daylight: 16"/66", Screw size: 4", Maco 8000 control
73	5	Pallets of Assorted Injection Mold Spare Parts
74	8	Pallets of Assorted Cincinnati Injection Mold Spare Parts
88	3	20' Bag Hoppers with North American Electric Blowers, 3 HP, 3510 RPM, 208-230/460 V, 3 Ph.
104A		Expanding Foam Line
132	1	Lift Table
178	1	(1) Pallet of Assorted Brass Bolts
199	1	Remaining Contents of Maintenance Office to Include: (2) 4-Drawer Computer Desks, (1) 5-Drawer Computer Desk, (4) Shelving Units, (3) Filing Cabinets, Etc.

233	1	Deltech P15104 Compressed Air Dryer 150 PSIG Max Inlet Pressure, 460 V, 60 Hz, 3 Ph. S/N 97KP1638
235	1	AEC FC3015 Chiller 15 HP, 460 V, 60 Hz, 3 Ph. S/N 96D0585
236	1	AEC FC3015 Chiller 15 HP, 460 V, 60 Hz, 3 Ph.
237	1	Tower Water System with (2) Baldor, (1) Unknown, (2) WEG Motors, (5) Paco Pumps
238	1	Water Pump Station with (2) AMT Motors, (2) Weg Motors, (4) AMT Pumps
239	1	Multistack MS90R1H1W Chiller 460 V, 3 Ph., 60 Hz, RLA 109A LRA 423A/Compressor
241	1	Ingersoll and Rand SSR-EP200 200 HP Compressor 892 CFM Capacity, 125 PSIG Operating Pressure, 128 Max Discharge Pressure, 135 PSIG Max Modulate Pressure, 7.5 HP Nominal Fan Motor, 460 V, 60 Hz, 3 Ph. S/N F11169U95018
279	1	Remaining Contents of Office Area to Include: (2) 2-Drawer Computer Desks, (1) Computer Desk, (1) Mini Fridge, (4) Filing Cabinets, (1) Horizontal Filing Cabinet, Etc.